


## E-glass Multiaxial Fabrics

Product Code: E-BXM800/225

Version: 2015

Page 1 of 1



## E-BXM800/225

Fiber Type: E-Glass

Architecture: Double Biaxial( $\pm 45^\circ$ ) With Mat

Total Weight: 30.53oz/sq.yd / 1035 g/sq.m

Roll Specifications			Fiber Architecture Data
Roll Width	Roll Weight	Roll Length	+45°: 11.83oz/sq.yd / 401 g/sq.m
50 in. / 1270 mm	110 lbs / 50 kg	41 yd / 38 m	-45°: 11.83oz/sq.yd / 401 g/sq.m
Acceptance Limits:			Mat: 6.64oz/sq.yd / 225 g/sq.m
± 5 mm	± 2%	± 0.5 m	
Technical Parameters			
Area Weight	Moisture Content	Loss on Ignition	
(g/m <sup>2</sup> )	(%)	(%)	
1035 ( ±5% )	≤ 0.20	0.2—1.0	

\*Packaging: Bag with polyester film, Carton on Pallet.

\*\*Total weight refers to reinforcement material only (does not include stitching weight).

\*\*\*Storage: Unless otherwise specified, fiberglass products should be stored in a dry, cool and rain-proof area. The room temperature and humidity should be always maintained at 15°C~35°C and 35%~65% respectively.